



1. TEMPORARY PAVEMENT REPLACEMENT WILL BE ALLOWED ONLY WHEN ASPHALT PLANTS ARE NOT IN OPERATION. WHEN TEMP. PAVEMENT IS USED, CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE AND UPKEEP OF SAID PATCH UNTIL PERMENANT PATCH IS INSTALLED.
2. UPON THE AVAILABILITY OF ASPHALT, THE CONTRACTOR SHALL EXCAVATE THE "K-KRETE" BACKFILL TO THE ORDERED DEPTH AND REPLACE WITH 4000 PSI CONCRETE AND THE REQUIRED 2" THICK ASPHALT TO THE LIMITS AND SPECIFICATIONS AS SHOWN.
3. STEEL PLATES OF ADEQUATE SIZE SHALL BE PLACED OVER ALL TRENCHES UNTIL THE 4000 PSI CONCRETE PLUG IS DEEMED PASSABLE.
4. STEEL PLATES SHALL BE PINNED AS REQUIRED TO PREVENT MOVEMENT. DURING WINTER ALL STEEL PLATES SHALL BE RECESSED.

## DETAIL OF PERMENANT CONCRETE PAVEMENT REPLACEMENT FOR COUNTY ROADS

COUNTY OF WESTCHESTER DEPARTMENT OF PUBLIC WORKS DIVISION OF ROAD MAINTENANCE	DATE:	10/29/08	PAGE NUMBER:	x of x
	DRAWN BY:		SCALE:	N.T.S.
WCDPW ROADWAY STANDARD DETAILS PERMENANT CONCRETE PAVEMENT REPLACEMENT DETAILS WESTCHESTER COUNTY, NY		FILENAME.EXT:		